



Batteries for Motorola CP040 / 140 / DP1400

Nova Code: **BAT-110** Series

- Charging options - 6 Way Intelligent Charger
 - Rapid Rate
 - Standard Rate
- Various capacities and chemistries available
- Guaranteed to comply with the original specifications
- Cell origin – Japan



Electrical Data	BAT-110E	BAT-110	BAT-110HH
Rated Capacity	1300 mAh	1500 mAh	2100 mAh
Voltage	7.5V (6 cells @ 1.25V each)		
Chemistry	NiMH	NiMH	NiMH
Charging Rate:			
6 Way Charger	2 Hours	2 Hours	3 Hours
Rapid Rate	2 Hours	2 Hours	3 Hours
Standard Rate	7 Hours	8 Hours	12Hours

Internal Circuitry **Flexible PC Board Incorporating:**

Negative temperature coefficient thermistor – controls temp.

Diode – protects reverse circuit

Polyswitch – 2 component design eliminates shorting

Mechanical Data			
Description	Bronze	Gold	Diamond
Belt Clip	NO	Includes a Belt hook device and stainless steel Spring loaded Hinge + Bracket	
Material	Arcylonitrile Butadiene Styrene – ABS		
Assembly	Using ultra sonic welding and silicon glue to embed the cells		
Quality Control	100% testing procedure		

Specification subject to change without notice. Issue 1

