



CCTV Video Balun HD - CVI/TVI/AHD

NOVA Code: **CAB-227**

- RJ45 Access

Features

- Compatible with all HD-CVI, HD-TVI, HD-AHD
- Up to 250m for 720P CVI Cameras
- Up to 120m for 1080P CVI Cameras
- Up to 250m for 720P TVI Cameras
- Up to 120m for 1080P TVI Cameras
- Up to 250m for 720P AHD Cameras
- Up to 120m for 1080P and Cameras
- Up to 300m for 960H Analog/CVBS Cameras
- Compact size and easy installation
- Built in transient suppression protection
- Join option Clip

Technical Specifications

Frequency Response	DC to 60 mHz	
Attenuation	0.5dB type	
CMRR	60dB	
Surge Protection	4KV ESD: 8KV	
Connectors	RCA to	Male BNC, Power Jack, Power Plug, Male BNC
Impedance	BNC: 75 Ohms Terminal: 100 Ohms	
Working Temperature	-10°C to +70°C	
Storage Temperature	-30°C to + 70°C	
Humidity	0 to 95%	
Dimension	39 x 17 x 19mm (excl. Connectors)	
Material	ABS Plastic	



Specification subject to change without notice. Issue 1



Tel: +27 11 719 0000
Fax: +27 11 444-2288
Web site: www.webb.co.za

+27 21 702 1580
+27 21 702 1585
www.rcw.co.za
clint@rcw.co.za

